

TECHNICAL SPECIFICATIONS

MACHINE	POUCH SIZE MIN.	POUCH SIZE MAX.	GUSSET MIN. /MAX.	MAX. VOLUME	OUTPUT R.P.M.	FILLING STATION	POUCH TYPE
H-360 S	120 x 150	360 x 300	—	2.000 c.c.	up to 70	3	Flat
H-360 D	90 x 100	180 x 300	—	1.000 c.c.	up to 140	3	Flat
H-360 FE	120 x 150	360 x 300	40 - 120	3.000 c.c.	60 - 65	3	Stand up
H-360 FED	90 x 100	180 x 300	40 - 120	1.500 c.c.	120 - 130	3	Stand up
H-360 FET	80 x 100	120 x 300	40 - 70	750 c.c.	180 - 195	3	Stand up
H-360 FEQ	70 x 100	90 x 300	40 - 50	350 c.c.	240 - 260	3	Stand up
H-360 /3	50 x 50	120 x 240	—	300 c.c.	up to 240	1	Flat
H-360 /4	50 x 50	90 x 240	—	250 c.c.	up to 320	1	Flat

Final speed will depend on product and film characteristics

Noise level < 70-80 Db	Max. Reel dimensions 800/600 mm. Ø	Electrical consumption 20-25 Kw	Reel core 76 (3")/152 (6") mm. Ø	Air consumption 150-800 l/min	Air pressure 6 bar
---------------------------	---------------------------------------	------------------------------------	-------------------------------------	----------------------------------	-----------------------

TRIPLEX RETORT EXECUTION

The technology used incorporates both, simplicity and heavy duty construction, to enable maximum efficiency and minimum downtime.

Flexibility is another main aspect, as using the same machine it is possible to make a wide range of different pack presentations.

Change over simplicity and rapidity from one product to another or from size to size, makes Mespac machines unique with respect to any existing competitive machine.

