

TECHNICAL SPECIFICATIONS

MACHINE	POUCH SIZE MIN.	POUCH SIZE MAX.	GUSSET MIN. /MAX.	MAX. VOLUME	OUTPUT RPM.	FILLING STATION	POUCH TYPE
H-570 S	150 x 200	570 x 400	—	11.000 c.c.	60 - 70	1 - 2	Flat
H-570 D	150 x 200	285 x 400	—	4.000 c.c.	120 - 140	1 - 2	Flat
H-570 /3	120 x 150	190 x 400	—	2.000 c.c.	180 - 210	1 - 2	Flat
H-570 FE	150 x 200	570 x 400	40 - 120	16.000 c.c.	50 - 60	1 - 2	Stand up
H-570 FED	150 x 200	285 x 400	40 - 120	5.500 c.c.	100 - 120	1 - 2	Stand up
H-570 FET	120 x 150	190 x 400	40 - 120	2.500 c.c.	150 - 180	1 - 2	Stand up

Final speed will depend on product and film characteristics

Noise level < 70-80 Db	Max. Reel dimensions 800/600 mm. Ø	Electrical consumption 30-35 Kw	Reel core 76 (3")/152 (6") mm. Ø	Air consumption 150-700 l/min	Air pressure 6 bar
---------------------------	---------------------------------------	------------------------------------	-------------------------------------	----------------------------------	-----------------------

TRIPLEX FEATURES

UP TO 190 MM

WIDTH POUCHES

The technology used incorporates both, simplicity and heavy duty construction, to enable maximum efficiency and minimum downtime.

Flexibility is another main aspect, as using the same machine it is possible to make a wide range of different pack presentations.

Change over simplicity and rapidity from one product to another or from size to size, makes Mespac machines unique with respect to any existing competitive machine.

