



Connect | Automate | Simplify 3350 3350 Smart Focus With unparalleled digitally-enabled This advanced model not only offers capabilities, this 30-watt CO, laser all the features of the 3350 but also is the ultimate solution for marking caters to the growing demand for complex and high-quality codes automation and flexibility. Equipped at lightning-fast speeds in various with cutting-edge automatic and industries such as food, beverage, dynamic marking capabilities, cosmetics, pharmaceutical, and it allows for seamless product changeovers without any manual extrusion. It allows for virtually unlimited font, code, and graphic intervention, thereby supporting your options and boasts impressive line journey towards Industry 4.0. speeds of up to 900 m/min. 3350 DEOJET.


Improve your uptime while delivering unmatched print quality

The 3350 series benefits

- High-speed marking capability prints up to 2,000 characters per second of text, bar codes, graphics, and other information
- High-resolution marking head delivers high-quality and permanent codes to support product traceability and anti-counterfeiting
- Variety of lenses deliver one of the largest marking areas while options like beam turning unit options simplify integration
- Multiple marking heads and wavelengths provide the flexibility to code a wide range of materials such as plastics, wood, glass, ceramics, and coated metals
- Up to 45,000 hours of laser source life expectancy offers extended operational life, reliable performance, and reduced cost of ownership
- Air-cooled laser source helps reduce maintenance intervals and additional costs
- Wi-Fi and cellular* connectivity capabilities offer advanced remote services to improve printer availability and OEE

*Subject to availability in your country

Multi-level surface marking



Mark different-sized products in the same marking field with 2.5D technology. You can save time and more easily manage complex marking.

Precise and permanent marking on a broad range of product and packaging materials



Beverage – plastic




Beverage – glass



Personal care – plastic

The Smart Focus feature helps you reduce manual intervention and get you one step closer to an automated production line


Auto-adjustable focal distance



Automatically adjust the focal distance after initial job setup without moving the laser system up and down, reducing errors and user intervention.

Uniform flat field correction






Best by: 11/12/25


Maintain exceptional print quality with a uniform spot-size marking across the entire field, with no degradation at the edge.

Pilot beam focus finder



Validate if your laser is focused and positioned correctly, so you can speed up your setup time. Right working distance and right alignment.

Flexible range and size mode



Size mode Max 42 mm Range mode Max 50 mm

Effortlessly alternate between greater focal distance range or an expanded marking field size, allowing for the completion of a diverse array of jobs.



Extrusion – PVC



Food - Paper label



Pharmaceutical - paper board

Pathway to productivity


Benefit from Videojet Born Digital solutions that help minimize IT cost and workload, improve printer availability, and boost overall equipment efficiency

The easy and secure way to wirelessly communicate, manage automatic software updates, and reduce installation time by up to 33%



Wi-Fi and cellular communication

Wi-Fi and cellular* connections, which are in an access box, satisfy IT standards and offer seamless software updates and fewer service interactions while improving overall equipment efficiency with access to more information.



Remote interface control

Webserver capability allows customers to access printers via supported web browsers on host computers. Up to five web server sessions are allowed for each printer.

On-demand remote technical support and advanced troubleshooting to anticipate potential printer issues in time and enable fast recovery



First-to-react

Real-time remote visibility

VideojetConnect™ Remote Service* provides real-time information on printer issues, allowing both Videojet experts and your technicians to monitor equipment status, troubleshoot issues, and improve long-term performance.

Simplified usability

Speed up equipment set-up and enjoy seamless integration into your line with easy beam positioning exactly where you need it

- Intuitive web-based user interface combined with a range of laser controller units, allows for simple operation and message creation and helps to ensure seamless production
- Detachable umbilical cable for faster setup, easy redeployment, and simple-to-use accessories connections
- Flexible marking head, including 32 standard beam delivery options (3350) or 0° to 90° rotation without the need for additional parts (3350 Smart Focus)
- Operator interface options and a choice of networking communications to match your preferred workflow

Technology to help meet your sustainability objectives

The Videojet laser portfolio delivers the flexibility to stay ahead of constantly evolving sustainability regulations and the resultant marking needs.

As the packaging industry moves towards the use of more sustainable materials, our broad portfolio of CO₂, fiber, and UV laser technologies – combined with our deep expertise and unique integration solutions – can help you meet developing requirements.

Our proprietary galvo control gives operators a speed advantage, either

marking more products with a single laser or minimizing the time the laser is in use, reducing energy consumption in both cases.

Videojet laser printers are also virtually maintenance-free, which helps maximize your machine's availability, delivering the highest OEE and lowest waste coding alternative.







| Model name | 3350 | 3350 Smart Focus |
|-----------------------------|--|--|
| Laser power | 30W | |
| Laser tube | Sealed CO ₂ laser | |
| Wavelengths | 9.3µm, 10.2µm and 10.6µm | |
| Sealing | Marking Unit and Supply Unit: IP54, optional IP65 | |
| Marking speed | Up to 2,000 characters/sec (1) | |
| Line Speed | Up to 15m/sec (49ft/sec) | |
| Beam exit options | 90° and straight-out | |
| Marking heads | SHC-60, SHC-100, SHC-150 | SHC-SF |
| Focusing method | Focusing lens | Dynamic telescope |
| Marking field | Min 30.8 x 38.2mm ² Max 601.0 x 439.8mm ² | Min. 52.72 x 129.35 mm ² Max. 70.79 x 178.42 mm ² |
| Focal lengths | 64/ 95/ 127/ 190/ 254 mm (2.5/ 3.75/ 5.0/ 7.5/ 10.0 inches) 63.5/ 85/ 100/ 150/ 200/ 300/ 351/ 400 mm (2.50/ 3.35/ 3.94 / 5.9/ 7.87/ 11.8/ 13.8/ 15.75 inches) 400/ 500/ 600 mm (15.75/ 19.68/ 23.62 inches) | 94 - 144 mm (3.7 to 5.6 inches) |
| Adjustable focal distancing | Not available | V |
| Multi-level marking | Not available | V |
| Flat field correction | Not available | V |
| Pilot laser integrated | Optional | V |
| Pilot beam Focus finder | Not available | V |
| Flexible Range-Size mode | Not available | V |
| Dynamic product change-over | Not available | V |
| Rotate head in 90° raster | √ | V |
| BTU (32 rotations) | V | Not available |
| Connectivity - Cellular | Standard* | Standard* |
| Connectivity - Wi-Fi | Standard* | Standard* |
| Operator interface options | TCS+ Touch control software / CLARiTY™ control software / Smart Graph | |
| Marking format | - Standard industrial fonts (Type 1 Windows® TrueType®) and Single line fonts Machine-readable codes (OCR, 2D-matrix, etc.) - Bar codes: BC25, BC251, BC39, BC128, GS1-128, EAN13, UPC_A, RSS14, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omnidirectional, RSS Limited, RSS Expanded, etc 2D codes: DataMatrix, DMRE, GS1, QR - Graphics, logos, symbols, etc Linear, circular, angular, reverse, rotate - Sequential and batch numbering - Automatic date, layer, and time coding; real-time clock - Dot mode enables marking 2D codes faster than traditional grid mode | |
| Languages | Support for 30 languages Additional languages available with Smart Graph software | |

^{*} Subject to availability in your country

+622158303560 info@markindo.co.id www.markindo.co.id

Videojet Technologies Inc. PT. Markindo Rekateknik Graha Arteri Mas 2, JI Panjang No 68, Kav 6 Jakarta Barat, DKI Jakarta



 $@2023\ Videojet\ Technologies\ Inc. --- All\ rights\ reserved.$

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice.

Part No. SL000721 br-3350-us-0623 Printed in U.S.A.



⁽¹⁾ Maximum marking and line speed is application dependent